

API / User

Last Modified on 11/14/2022 11:09 am EST

Entity Description:

User is the information about the User that is used in PoliteMail for sending email and Metric information.

PoliteMail also defines the User a Role in the system and level of access and sharing the user has within the system. There are three User types: Administrator, Manager, and User.

Properties

Name	Description	Type	Additional Information
ID		Int32	
FirstName		String	
LastName		String	
Name		String	
Email		String	
Phone		String	
Cell		String	
Fax		String	
LastLogin		DateTime	
UserType		Int16	
BusinessID		Int32	
RegionID		Int32	

Entity Statement

if you are using versions **earlier than 5.0**, substitute "ssv3" for "api" for each Request listed below.

Creating an User

Request

POST /api/odata/Users

Content-Type

application/json

Request body

```
{
  "ID": "0", "FirstName": "Example First Name", "LastName": "Example Last Name",
  "Name": "New User", "Email": "Example Email", "Phone": "(000) 000-0000",
  "Cell": "(000) 000-0000", "Fax": "(000) 000-0000", "LastLogin": "2014-12-
  02T12:00:00.000Z", "UserType": "0", "BusinessID": "0", "RegionID": "0"
}
```

Response body

```
{
  "ID":1,"FirstName":"Example First Name","LastName":"Example Last Name",
  "Name":"New User","Email":"Example Email","Phone":(000) 000-0000,
  "Cell":(000) 000-0000,"Fax":(000) 000-0000,"LastLogin":"2014-12-
  03T15:42:02.125Z","UserType":0,"BusinessID":0,"RegionID":0
}
```

Deleting an User

Request

```
DELETE /api/odata/Users(1)
```

Response Headers

```
HTTP/1.1 204 No Content
```

Getting an User

Request

```
GET /api/odata/Users(1)
```

Content-Type

```
application/json
```

Response body

```
{
  "ID":1,"FirstName":"Example First Name","LastName":"Example Last Name",
  "Name":"New User","Email":"Example Email","Phone":(000) 000-0000,
  "Cell":(000) 000-0000,"Fax":(000) 000-0000,"LastLogin":"2014-12-
  03T15:42:02.125Z","UserType":0,"BusinessID":0,"RegionID":0
}
```

Updating a User

Request

```
PUT /api/odata/Users(1)
```

Content-Type

```
application/json
```

Request body

```
{
  "ID":"0","FirstName":"Example First Name","LastName":
  "Example Last Name","Name":"New User","Email":"Example Email",
  "Phone":"(000) 000-0000","Cell":"(000) 000-0000","Fax":"(000) 000-0000",
  "LastLogin":"2014-12-02T12:00:00.000Z","UserType":"0",
  "BusinessID":"0","RegionID":"0"
}
```

Response Headers

```
HTTP/1.1 204 No Content
```

Getting all Users

Request

```
GET /api/odata/Users
```

Content-Type

```
application/json
```

Response body

```
"value":[{
  "ID":0,"FirstName":"Example First Name","LastName":"Example Last Name",
  "Name":"New User","Email":"Example Email","Phone":(000) 000-0000,
  "Cell):(000) 000-0000,"Fax):(000) 000-0000,"LastLogin":"2014-12-
  02T12:00:00.000Z","UserType":0,"BusinessID":0,"RegionID":0
},{
  "ID":1,"FirstName":"Example First Name","LastName":"Example Last Name",
  "Name":"New User","Email":"Example Email","Phone":(000) 000-0000,
  "Cell):(000) 000-0000,"Fax):(000) 000-0000,"LastLogin":"2014-12-
  03T15:42:02.125Z","UserType":0,"BusinessID":0,"RegionID":0
}]
```

PoliteMail