

API / Template

Last Modified on 11/14/2022 11:07 am EST

Entity Description:

Template entity provides users the capability to design professional looking templates that can be used and modified for totally customizable email messages. The templates are saved and can be reused in other mailings.

Properties

Name	Description	Type	Additional Information
ID		Int32	
ActiveState		Int16	
Name		String	
Description		String	
OwnerID		Int32	
Body		String	
BodyBinary		Binary	
Icon		Bitmap	
LastUsed		DateTime	
CreationDate		DateTime	
Subject		String	
Shared		Boolean	
BusinessID		Int32	
RegionID		Int32	

Entity Statement

if you are using versions **earlier than 5.0**, substitute "ssv3" for "api" for each Request listed below.

Creating a Template

Request

POST /api/odata/Templates

Content-Type

application/json

Request body

```
{
  "ID": "0", "ActiveState": "1", "Name": "New Template", "Description":
  "Example Description", "OwnerID": "0", "Body": "Example Body",
  "BodyBinary": "0", "Icon": "Example Icon", "LastUsed": "2014-12-
  10T10:48:26.155Z", "CreationDate": "2014-12-01T01:00:25.155Z",
  "Subject": "Example Subject", "Shared": false, "BusinessID": "0", "RegionID": "0"
}
```

Response body

```
{
  "ID":1,"ActiveState":1,"Name":"New Template","Description":"Example
  Description","OwnerID":0,"Body":"Example Body","BodyBinary":0,
  "Icon":"Example Icon","LastUsed":"2014-12-09T04:40:08.155Z",
  "CreationDate":"2014-12-08T13:30:25.125Z","Subject":"Example
  Subject","Shared":false,"BusinessID":0,"RegionID":0
}
```

Deleting a Template

Request

```
DELETE /api/odata/Templates(1)
```

Response Headers

```
HTTP/1.1 204 No Content
```

Getting a Template

Request

```
GET /api/odata/Templates(1)
```

Content-Type

```
application/json
```

Response body

```
{
  "ID":1,"ActiveState":1,"Name":"New Template","Description":
  "Example Description","OwnerID":0,"Body":"Example Body",
  "BodyBinary":0, "Icon":"Example Icon","LastUsed":"2014-12-
  09T04:40:08.155Z","CreationDate":"2014-12-08T13:30:25.125Z",
  "Subject":"Example Subject","Shared":false,"BusinessID":0,"RegionID":0
}
```

Updating a Template

Request

```
PUT /api/odata/Templates(1)
```

Content-Type

```
application/json
```

Request body

```
{
  "ID":"0","ActiveState":"1","Name":"New Template","Description":
  "Example Description","OwnerID":"0","Body":"Example Body",
  "BodyBinary":"0", "Icon":"Example Icon","LastUsed":"2014-12-
  10T10:48:26.155Z","CreationDate":"2014-12-01T01:00:25.155Z",
  "Subject":"Example Subject","Shared":false,"BusinessID":"0","RegionID":"0"
}
```

Response Headers

```
HTTP/1.1 204 No Content
```

Getting all Templates

Request

```
GET /api/odata/Templates
```

Content-Type

```
application/json
```

Response body

```
“value”:[{
  “ID”:0,“ActiveState”:1,“Name”：“New Template”,“Description”:
  “Example Description”,“OwnerID”:0,“Body”：“Example Body”,
  “BodyBinary”:0, “Icon”：“Example Icon”,“LastUsed”：“2014-12-
  10T10:48:26.155Z”,“CreationDate”：“2014-12-01T01:00:25.155Z”,
  “Subject”：“Example Subject”,“Shared”:false,“BusinessID”:0,“RegionID”:0
},{
  “ID”:1,“ActiveState”:1,“Name”：“New Template”,“Description”:
  “Example Description”,“OwnerID”:0,“Body”：“Example Body”,
  “BodyBinary”:0, “Icon”：“Example Icon”,“LastUsed”：“2014-12-
  09T04:40:08.155Z”,“CreationDate”：“2014-12-08T13:30:25.125Z”,
  “Subject”：“Example Subject”,“Shared”:false,“BusinessID”:0,“RegionID”:0
}]
```

PoliteMail