

# API / SmartAttachment

Last Modified on 11/14/2022 10:59 am EST

## Entity Description:

PoliteMail's SmartAttachment enables email attachments to be tracked to know who is opening the email messages. SmartAttachment is inserted into the email as a link and the file is uploaded to the Content Library.

## Properties

Name	Description	Type	Additional Information
ID		Int32	
ActiveState		Int16	
Name		String	
Description		String	
URL		String	
OwnerID		Int32	
GUID		String	
Shared		Boolean	
CreationDate		DateTime	
Data		Binary	
ContentType		String	
BusinessID		Int32	
RegionID		Int32	

## Entity Statement

if you are using versions **earlier than 5.0**, substitute "ssv3" for "api" for each Request listed below.

### Creating a SmartAttachment

#### Request

POST /api/odata/SmartAttachments

#### Content-Type

application/json

#### Request body

```
{
  "ID": "0", "ActiveState": "1", "Name": "New Attachment",
  "Description": "", "URL": "Example RL", "OwnerID": "0", "GUID":
  "0", "Shared": false, "CreationDate": "2014-12-10T17:48:26.155Z",
  "Data": "0", "ContentType": "Example Content Type", "BusinessID":
  "0", "RegionID": "0"
}
```

#### Response body

```
{
  "ID":1,"ActiveState":1,"Name":"New Attachment","Description":
  "", "URL":"Example URL", "OwnerID":"0", "GUID":"0", "Shared":false,
  "CreationDate":"2014-12-10T18:08:11.125Z", "Data":0, "ContentType":
  "Example Content Type", "BusinessID":0, "RegionID":0
}
```

### Deleting a SmartAttachment

#### Request

```
DELETE /api/odata/SmartAttachments(1)
```

#### Response Headers

```
HTTP/1.1 204 No Content
```

### Getting a SmartAttachment

#### Request

```
GET /api/odata/SmartAttachments(1)
```

#### Content-Type

```
application/json
```

#### Response body

```
{
  "ID":1,"ActiveState":1,"Name":"New Attachment","Description":
  "", "URL":"Example URL", "OwnerID":"0", "GUID":"0", "Shared":false,
  "CreationDate":"2014-12-10T18:08:11.125Z", "Data":0, "ContentType":
  "Example Content Type", "BusinessID":0, "RegionID":0
}
```

### Updating a SmartAttachment

#### Request

```
PUT /api/odata/SmartAttachments(1)
```

#### Content-Type

```
application/json
```

#### Request body

```
{
  "ID":"0", "ActiveState":"1", "Name":"New Attachment", "Description":
  "", "URL":"Example URL", "OwnerID":"0", "GUID":"0", "Shared":false,
  "CreationDate":"2014-12-10T17:48:26.155Z", "Data":"0",
  "ContentType":"Example Content Type", "BusinessID":"0", "RegionID":"0"
}
```

#### Response Headers

```
HTTP/1.1 204 No Content
```

### Getting all SmartAttachments

#### Request

```
GET /api/odata/SmartAttachments
```

#### Content-Type

```
application/json
```

#### Response body

```
"value":[{
  "ID":0,"ActiveState":1,"Name":"New Attachment","Description":
  "", "URL":"Example URL","OwnerID":0,"GUID":"0","Shared":false,
  "CreationDate":"2014-12-10T17:48:26.155Z","Data":0,"ContentType":
  "Example Content Type","BusinessID":0,"RegionID":0
},{
  "ID":1,"ActiveState":1,"Name":"New Attachment","Description":
  "", "URL":"Example URL","OwnerID":0,"GUID":"0","Shared":false,
  "CreationDate":"2014-12-10T18:08:11.125Z","Data":0,"ContentType":
  "Example Content Type","BusinessID":0,"RegionID":0
}]
```

PoliteMail