

# API / CustomField

Last Modified on 11/14/2022 10:32 am EST

## Entity Description:

Custom Field allows a user to further customize the custom fields in the PoliteMail Personalization feature (e.g. salutation, birthdate, department, etc...). Custom Field may also be used for Personalization merge fields within the New PoliteMail Message editor.

## Properties

Name	Description	Type	Additional Information
ID		Int32	
Name		String	
Show		Boolean	

## Entity Statement

if you are using versions **earlier than 5.0**, substitute "ssv3" for "api" for each Request listed below.

### Creating a CustomField

#### Request

POST /api/odata/CustomFields

#### Content-Type

application/json

#### Request body

```
{
  "ID": "0", "Name": "New Field", "Show": true
}
```

#### Response body

```
{
  "ID": 1, "Name": "New Field", "Show": true
}
```

### Deleting a CustomField

#### Request

DELETE /api/odata/CustomFields(1)

#### Response Headers

HTTP/1.1 204 No Content

### Getting a List

#### Request

GET /api/odata/CustomFields(1)

**Content-Type**

application/json

**Response body**

```
{
  "ID":1,"Name":"New Field","Show":true
}
```

**Updating a CustomField****Request**

PUT /api/odata/CustomFields(1)

**Content-Type**

application/json

**Request body**

```
{
  "ID":"0","Name":"New Field","Show":true
}
```

**Response Headers**

HTTP/1.1 204 No Content

**Getting all Lists****Request**

GET /api/odata/CustomFields

**Content-Type**

application/json

**Response body**

```
"value":[{"
  "ID":0,"Name":"New Field","Show":true
},{
  "ID":1,"Name":"New Field","Show":true
}]
```