

API / Message

Last Modified on 10/20/2025 10:49 am EDT

Entity Description:

All PoliteMail Messages distributed are tracked as groups of emails (e.g. distribution list or Templates) and a record of interactions with the recipients and the Email is stored and the metadata parsed to capture the metrics for future analysis.

Properties

Name	Description	Type	Additional Information
ID		Int32	
Subject		String	
OwnerID		Int32	
SendMode		Int32	
SendDate		DateTime	

Entity Statement



if you are using versions **earlier than 5.0**, substitute "ssv3" for "api" for each Request listed below.

Creating a Message

Request

POST /api/odata/Messages

Content-Type

application/json

Request body

```
{
  "ID": "0", "Subject": "Example
Subject", "OwnerID": "0", "SendMode": "0", "SendDate": "2014-12-
01T12:48:26.155Z"
}
```

Response body

```
{
  "ID": "1", "Subject": "Example
Subject", "OwnerID": "0", "SendMode": "0", "SendDate": "2014-12-01T13:02:12.145Z"
}
```

Deleting a Message

Request

DELETE /api/odata/Messages(1)

Response Headers

HTTP/1.1 204 No Content

Getting a Message

Request

GET /api/odata/Messages(1)

Content-Type

application/json

Response body

```
{
  "ID":1,"Subject":"Example
  Subject","OwnerID":0,"SendMode":0,"SendDate":"2014-12-01T13:02:12.145Z"
}
```

Updating a Message

Request

PUT /api/odata/Messages(1)

Content-Type

application/json

Request body

```
{
  "ID":"0","Subject":"Example
  Subject","OwnerID":"0","SendMode":"0","SendDate":"2014-12-
  01T12:48:26.155Z"
}
```

Response Headers

HTTP/1.1 204 No Content

Getting all Messages

Request

GET /api/odata/Messages

Content-Type

application/json

Response body

```
"value":[{
  "ID":0,"Subject":"Example
  Subject","OwnerID":0,"SendMode":0,"SendDate":"2014-12-01T12:48:26.155Z"
},{
  "ID":1,"Subject":"Example
  Subject","OwnerID":0,"SendMode":0,"SendDate":"2014-12-01T13:02:12.145Z"
}]
```