

API / CustomField

Last Modified on 10/20/2025 10:49 am EDT

Entity Description:

Custom Field allows a user to further customize the custom fields in the PoliteMail Personalization feature (e.g. salutation, birthdate, department, etc...). Custom Field may also be used for Personalization merge fields within the New PoliteMail Message editor.

Properties

Name	Description	Type	Additional Information
ID		Int32	
Name		String	
Show		Boolean	

Entity Statement



if you are using versions earlier than 5.0, substitute "ssv3" for "api" for each Request listed below.

Creating a CustomField

Request

POST /api/odata/CustomFields

Content-Type

application/json

Request body

```
{
  "ID": "0", "Name": "New Field", "Show": true
}
```

Response body

```
{
  "ID": 1, "Name": "New Field", "Show": true
}
```

Deleting a CustomField

Request

DELETE /api/odata/CustomFields(1)

Response Headers

HTTP/1.1 204 No Content

Getting a List

Request

GET /api/odata/CustomFields(1)

Content-Type

application/json

Response body

```
{  
  "ID":1,"Name":"New Field","Show":true  
}
```

Updating a CustomField

Request

PUT /api/odata/CustomFields(1)

Content-Type

application/json

Request body

```
{  
  "ID":"0","Name":"New Field","Show":true  
}
```

Response Headers

HTTP/1.1 204 No Content

Getting all Lists

Request

GET /api/odata/CustomFields

Content-Type

application/json

Response body

```
"value":[{  
  "ID":0,"Name":"New Field","Show":true  
},{  
  "ID":1,"Name":"New Field","Show":true  
}]
```