

API / Category

Last Modified on 10/20/2025 10:44 am EDT

Entity Description:

Contacts can be organized outside of mailing lists using category. Categories are assigned manually to individual contacts, or when selecting or importing a list or group of contacts.

Properties

Name	Description	Type	Additional Information
ID		Int32	
Name		String	
Enabled		Int32	

Entity Statement

Creating a Category

Request

POST /api/odata/Categories (for versions before 5.0, substitute "ssv3" for "api")

Content-Type

application/json

Request body

```
{
  "ID": "0", "Name": "New Category", "Enabled": "0"
}
```

Response body

```
{
  "ID": "1", "Name": "New Category", "Enabled": "0"
}
```

Deleting a Category

Request

DELETE /ssv3/odata/Categories(1) (for versions before 5.0, substitute "ssv3" for "api")

Response Headers

HTTP/1.1 204 No Content

Getting a Category

Request

GET /ssv3/odata/Categories(1) (for versions before 5.0, substitute "ssv3" for "api")

Content-Type

application/json

Response body

```
{
  "ID":1,"Name":"New Category","Enabled":0
}
```

Updating a Category

Request

PUT /ssv3/odata/Categories(1) (for versions before 5.0, substitute "ssv3" for "api")

Content-Type

application/json

Request body

```
{
  "ID":0,"Name":"New Category","Enabled":0
}
```

Response Headers

HTTP/1.1 204 No Content

Getting all Categories

Request

GET /ssv3/odata/Categories (for versions before 5.0, substitute "ssv3" for "api")

Content-Type

application/json

Response body

```
"value":[{
  "ID":0,"Name":"New Category","Enabled":0
},{
  "ID":1,"Name":"New Category","Enabled":0
}]
```